

**MADE IN FRANCE** 

**Regulatory information**

CE Marking	Index of classification	Notified body	<del>PHTALATES LATEX</del>
CE 0459	Ila	G-MED	



**Technical characteristics Easy Pump G10803**

STORAGE CONDITIONS	T : -5°à 40°C, Humidity : 20- 80 %
CONDITIONS OF USE	T : 5°à 40°C, Humidity : 20 – 80 % Maximum altitude 2000 m Atmospheric pressure 79.0 kPa to 106 kPa
CASE MATERIALS	ABS (Acrylonitrile Butadiene Styrene)
Density	1.112 g/ cm <sup>3</sup>
Shock resistance	> 25 KJ / m <sup>2</sup>
UL flammability test	UL94 V-0
Heat stability	85°C
Hardness	78
DIMENSIONS	CASE
Height (mm)	250
Width (mm)	300
Depth (mm)	190
	SCREEN
Width (mm)	120
Height (mm)	90
WEIGHT kg	4.2 KGS
LINE VOLTAGE	100 - 240 V AC
LINE FREQUENCY	50 – 60 Hz
POWER PLUG	60 VA
FUSE	
Input power card	FT2AH/250V
Output power card	F3.15AH/15V
Battery	F8AH/12V
PULSED POWER SUPPLY	Entry : 90-264 Vac, 47-63 Hz, 1.8 – 1 A Exit : 15 Vdc, 4A
BATTERY	Rechargeable
Type	Pb
Voltage	12 Volts
Ampere	4000 mAh
Charging time	8 h
Autonomy	10 h
PUMP	
Type	Membrane pump
Pump flow	4.6 l/mn

**DDM**

DESSILLONS &amp; DUTRILLAUX

**TECHNICAL CHARACTERISTICS**

CT 047

Pneumatic tourniquet G10803 Easy Pump 1  
tube

Index 7

PRESSION		
Type		1.7 bar
Service		0 to 600 mmHg
Setting range		± 1 mm Hg
Setting precision		± 5 mm Hg
		An audible and visual alarm
		1
TIMER		
Units		minutes
Alarm		Programmable audible and visual alarm
CONNECTION		
Pneumatic		1 female coupler CPC type
Electric		Connector CEE22
MAXIMUM SOUND LEVEL WHILE FUNCTIONING		52 dB

Dessillons &amp; Dutrillaux

Zone Industrielle La Tuque

Tél : +33 5 53 48 30 66

technique@ddmedical.fr

47240 CASTELCULIER

Fax : +33 5 53 47 24 64

www.ddmedical.fr

Date of first EC marking certificate :  
1998

Page 3 / 3